

### FABRENE® PIXEL™ 40 PE MEDIA

A medium weight, premium billboard grade PE reinforced media fabric.  
UV-Ready

<u>PROPERTY</u>	<u>UNIT</u>		<u>VALUES</u>	<u>TEST METHOD</u>
Unit Weight	oz/yd <sup>2</sup>		3.1	ASTM D3776
Warp Construction	Tapes/in	Warp	9.1	ASTM D3775
	Tapes/in	Weft	5.8	
Widths	in	up to	150	
Tensile Grab Strength	lbf	Warp	79	ASTM D751
	lbf	Weft	110	
Tear Strength (trapezoid)	lbf	Warp	20	ASTM D4533/D4851
	lbf	Weft	38	
Coating	mil	Silver	.8	ASTM D1777 MOD
	mil	White	.9	
Thickness	mil		5	Caliper

\* Includes force to shift tapes - Tear may be crosswise to direction of force.

Fabrene® PIXEL™ 40 PE Media contains some ultraviolet inhibitors and is designed for a 6-month outdoor exposure. For further information, contact your FABRENE Inc. representative.

Suggested Applications: Media substrate, banners, outdoor signage.

NOTE: These values are typical data and are not intended as limiting specifications.

Date: 15/09/30

#### SALES INQUIRIES

**Fabrene Inc.**  
Tel: (888) 322-7363 ext 234  
Tel: (705) 476-7057 ext 234  
Fax: (705) 476-7787

#### ORDER DESK

**North Bay, ON, Canada**  
Tel: (888) FABRENE  
(888) 322-7363  
ext. 222 or 226  
Fax: (705) 476-0665

#### MAILING ADDRESS

**Fabrene Inc.**  
240 Dupont Rd.  
P.O. Box 4040  
North Bay, ON, Canada  
P1B 9B4

