

## FABRENE® PIXEL™ 20 PE MEDIA

A light weight, billboard grade PE reinforced media fabric.  
UV-Ready

<u>PROPERTY</u>	<u>UNIT</u>		<u>VALUES</u>	<u>TEST METHOD</u>
Unit Weight	g/m <sup>2</sup>		90	ASTM D3776
Warp Construction	Tapes/10cm	Warp	36	ASTM D3775
	Tapes/10cm	Weft	13	
Widths	mm		up to 3810	
Tensile Grab Strength	Newton	Warp	310	ASTM D751
	Newton	Weft	310	
Tear Strength (trapezoid)	Newton	Warp	120	ASTM D4533/D4851
	Newton	Weft	120	
Coating	µm	Silver	20	ASTM D1777 MOD
	µm	White	21	
Thickness	µm		108	Caliper

\* Includes force to shift tapes - Tear may be crosswise to direction of force.

Fabrene® PIXEL™ 20 PE Media contains some ultraviolet inhibitors and is designed for a 6-month outdoor exposure. For further information, contact your FABRENE Inc. representative.

Suggested Applications: Media substrate

NOTE: These values are typical data and are not intended as limiting specifications.

### SALES INQUIRIES

**Fabrene Inc.**  
Tel: (888) 322-7363 ext 234  
Tel: (705) 476-7057 ext 234  
Fax: (705) 476-7787

### ORDER DESK

**North Bay, ON, Canada**  
Tel: (888) FABRENE  
(888) 322-7363  
ext. 222 or 226  
Fax: (705) 476-0665

### MAILING ADDRESS

**Fabrene Inc.**  
240 Dupont Rd.  
P.O. Box 4040  
North Bay, ON, Canada  
P1B 9B4

Date: 2015/09/30

